

Vinyl Finishes

Vinyl Designer Collection II Neutrals



HUF COR[®]

shaping your experience

CONTATTO

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



VINYL SPECIFICATIONS

Type II & Class A Patterns, Low VOC

Minimum Weight: 20 oz.

Average Width: 54" [1372mm]

CCFA-W-101: ✓

CCC-W-408A: ✓

MEA Approved N.Y. Dept of Building: ✓

NFPA 101-94 when tested by ASTM E84: ✓



CONTATTO

Backing:

» Osnaburg

Fire Hazard Classification results:

- ASTM E-84 Tunnel Test
- Flame Spread: 15
- Smoke Development: 20

JOLI

Backing:

» Poly Cotton Osnaburg

Fire Hazard Classification results:

- ASTM E-84 Tunnel Test
- Flame Spread: 20
- Smoke Development: 45

VENTO

Backing:

» Osnaburg

Fire Hazard Classification results:

- ASTM E-84 Tunnel Test
- Flame Spread: 5
- Smoke Development: 35

JOLI

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



VENTO

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



PRODUCT FEATURES

- » Compliant with CDPH/EHLB Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions
- » Antimicrobial (non-arsenic). This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall surfaces, particularly in warm, humid climates.
- » Compliant with California, Proposition 65
- » PFOA free-does not contain, nor will it degrade to, Perfluoro Octanoic Acid (PFOA)
- » NFPA 101 and IBC Class A interior wall finish rating when tested using ASTM-E84 method of reinforced cement board when tested in accordance with NFPA 286
- » Meets ISO 14064-1,2,3:2006 Greenhouse Gases

Hufcor's Designer Collection of vinyl finishes offer affordable options for upscale applications



CLEANING INSTRUCTIONS

- » Common dirt and stains may be removed from wallcovering by rubbing lightly with a moistened cloth or natural sponge using mild soap, detergent or non-abrasive cleanser. It is important that clean water be continuously used and that the material be towel dried.
- » **CAUTION:** Strong organic solvents (such as ketones) and harsh abrasive cleaners are not recommended. These materials will cause dulling, discoloration or softening of the vinyl, possibly resulting in permanent damage.



hmarketing@hufcor.com | (800) 542 2371
2101 Kennedy Rd. Janesville, WI 53545
HUF COR.COM